UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO.

: 7,040,586 B2

Page 1 of 2

DATED

APPLICATION NO.: 10/728593 : May 9, 2006

INVENTOR(S)

: Angelo Joseph Kusber et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 12

Line 7, delete "die", and insert therfor --the--.

Column 13

Line 23, delete "is achieved by the", and insert therefor -- is achieved by the first screw being configured such that threading on the first screw threadingly engages the outer perimeter of the first opening, the --.

Line 27, delete "is achieved by the", and insert therefor -- is achieved by the second screw being configured such that threading on the second screw threadingly engages the outer perimeter of the second opening, the --.

Line 40, delete "pre-disposed within the opening", and insert therefor -- pre-disposed and captivated within the opening, wherein captivation is achieved by the screw being configured such that threading on the screw threadingly engages the outer perimeter of the opening --.

Line 47, after "predisposed", and insert therefor -- and captivated --.

Column 14

Line 37, delete "pre-disposed within the first opening", and insert therefor -- predisposed and captivated within the first opening, wherein captivation is achieved by the first screw being configured such that threading on the first screw threadingly engages the outer perimeter of the first opening --.

UNITED STATES PATENT AND TRADEMARK OFFICE **CERTIFICATE OF CORRECTION**

PATENT NO.

: 7,040,586 B2

Page 2 of 2

DATED

APPLICATION NO.: 10/728593

INVENTOR(S)

: May 9, 2006 : Angelo Joseph Kusber et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Line 40, delete "pre-disposed within the second opening", and insert therefor -- predisposed and captivated within the second opening, wherein captivation is achieved by the second screw being configured such that threading on the second screw threadingly engages the outer perimeter of the second opening --.

This certificate supersedes Certificate of Correction issued September 5, 2006.

Signed and Sealed this

Seventh Day of November, 2006

JON W. DUDAS Director of the United States Patent and Trademark Office